

KEEP OUT OF REACH OF CHILDREN

BOND^{®1}

Adjuvant

Sticker, Deposition/Retention Agent

Contains: Synthetic latex and primary aliphatic oxyalkylated alcohol

NET CONTENTS:
5 Litres

Registered By:
Elliott Technologies Limited
45 Kitchener Road, Pukekohe, New Zealand.
Phone: 0800 100 325 www.elliott-technologies.co.nz

Elliott[®]

BOND^{®1}
Adjuvant

HSNO Class: 6.4A, 9.1C

HEALTH WARNING: HARMFUL – may cause eye irritation

ENVIRONMENTAL WARNING: HARMFUL to aquatic life with long-lasting effects. Avoid contamination of any water supply with product or empty container.

PRODUCT DISPOSAL: Ensure unwanted product is used by another operator strictly in accordance with label directions. Do not allow product to enter waterways, drains or sewers.

CONTAINER DISPOSAL: Ensure container is completely empty. Burn if permitted and circumstances, especially wind direction allow, otherwise bury in landfill.

HANDLING PRECAUTIONS: When mixing or applying, wear protective clothing, gloves and goggles. Do not eat or drink while using. Wash hands and face before meals and after work. Wash protective clothing after work.

STORAGE: Store in original container tightly closed and in a locked, dry, cool, well ventilated area, away from feed, seeds and foodstuffs. Storage must be generally in accordance with NZS8409 Management of Agrichemicals. See the HAZNOTE for further information.

FIRST AID: If swallowed do NOT induce vomiting. For advice, contact the National Poisons Centre 0800 POISON (0800 764 766) or a doctor immediately. If skin, hair or eye contact occurs, remove contaminated clothing and flush skin, hair and/or eyes with running water for several minutes.

PRODUCT INFORMATION

BOND is a very efficient sticker. BOND's adhesion properties increase initial deposition and reduce run-off during spraying. BOND should be applied 1 hour before rain and is rainfast as soon as it is dry. BOND has a unique network pattern on drying, allowing quicker release of systemic products into the leaves while still holding protective products in place on the leaf surface, extending their life by protecting the pesticide against rainfall, ultra-violet degradation, wind erosion and volatility. BOND is bio-degradable.

DIRECTIONS FOR USE

Half fill spray tank with water and, with agitation running, add the pesticides according to their labels. When the pesticides are thoroughly mixed, continue filling under agitation and add BOND at the desired rate.

RECOMMENDATIONS:

The sticking efficiency of BOND may vary according to the formulation of the pesticides and other additives. So the usage rate may need adjustment for different mixtures. Do not use BOND at rates above 5% (5 litres/100 litres water).

- Aerial application and low volume ground rigs – use 125 –250mls/litres water.
- Dilute ground rig spraying (250 –1000 litres/ha) – use 250-500 mls/ha

NOTES: 1. Observe the pre-harvest intervals on the pesticide labels.
2. Rinse tank, lines and nozzles immediately after spraying.

EXCLUSION OF LIABILITY: PLEASE READ

To the extent permitted by law, buyers and/or users of the goods accept that neither the manufacturer, Elliott Technologies Limited as distributor, nor any other distributor have any liability or responsibility whatsoever for any loss, damage or injury whether in contract or tort, whether direct, indirect or consequential howsoever arising in connection with the supply of these goods.

®1 - is a Registered Trademark of Loveland Products Inc.
© - is a registered Trademark of Elliott Technologies Ltd
HSNO Approval Code HSR002503

24 Hour Emergency Response

0800 CHEM CALL
0800 243 622

Registered By:
Elliott Technologies Limited
45 Kitchener Road
Pukekohe New Zealand.
Phone: 0800 100 325
www.elliott-technologies.co.nz

Batch No.

DOM



9 421022 420231

Elliott[®]

 PMS 297

 Black

 Pms 485